| 지시외 응접치수 | 지시외 모서리부분 |
|---|---|
| | 지시외일반 모서리제거 C = 0.3~1.2 R = 0.3~1.2 |

| 지시외치수허용차 | 절삭가공부분 | 구분 | 0.5 ~ 6 | 6 ~ 30 | 30 ~ 120 | 120 ~ 315 | 315 ~ 1000 | 1000 ~ 2000 |
|---|---|---|---|---|---|---|---|---|
| | | 급 | ±0.1 | ±0.2 | ±0.3 | ±0.5 | ±0.8 | ±1.2 |

| 표면거칠기 | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|
| Ra | √ | 25/ | 12.5/ | 6.3/ | 3.2/ | 1.6/ | 0.8/ | 0.2/ | 0.1/ |
| Rmax | | 100S | 50S | 25S | 12.5S | 6.3S | 3.2S | 0.8S | 0.4S |
| 다듬질 | ~ | ▽ | | ▽▽ | | ▽▽▽ | | ▽▽▽▽ | |

| NO. | DATE | REVISION & DESCRIPTION | SIGNATURE REVIEWED | SIGNATURE CHECKED |
|---|---|---|---|---|
| 1 | | | | |
| 2 | | | | |

# HYD' UNIT MODEL : NWHP-170L-LCP-SW













## NOTES

1. HYDRAULIC OIL: ISO VG.46
2. WORKING PRESSURE: 100bar
3. OIL FLOW: 10 L/min
4. OIL TANK: 170 LITER(S275)
5. POWER : **3ø 440V, 60HZ**
6. PANEL : LCP. POLE TYPE




## CIRCUIT DIAGRAM

| NO. | DESCRIPTION | MAT'(KS) | UNIT QUANTITY | TOTAL QUANTITY | PER UNIT WEIGHT(kg) | TOTAL WEIGHT(kg) | REMARK'S |
|---|---|---|---|---|---|---|---|
| 27 | LOCAL CONTROL PANEL | | 1 | | | | 500 x 550 x 250 |
| 26 | HAND PUMP | | 1 | | | | PMD-12-byB-S, 380bar |
| 25 | GATE VALVE | | 1 | | | | PT3/4" x 5bar |
| 24 | BALL VALVE | | 1 | | | | PT1/4" x 5bar |
| 23 | TEST POINT | | 1 | | | | PT1/4 x M16 x 2P |
| 22 | TEST POINT | | 6 | | | | G1/4 x M16 x 2P |
| 21 | TEST HOSE | | 2 | | | | M16x2P, 1000L |
| 20 | PRESSURE GAUGE | | 1 | | | | BD ø63 x 160BAR |
| 19 | PRESSURE SWITCH | | 1 | | | | DE6, 60bar |
| 18 | MICRO SEPARATOR | | 1 | | | | YMC-50 |
| 17 | SUCTION FILTER | | 1 | | | | SH-SE-04 |
| 16 | E-HEATER | | 1 | | | | 2.2KW, 3ø, 440V, 60HZ |
| 15 | TEMP. SWITCH | | 1 | | | | EGO-110 |
| 14 | LEVEL GAUGE | | 1 | | | | PLT2 |
| 13 | AIR BREATHER | | 1 | | | | TCAR-4080CB0 |
| 12 | LEVEL SWITCH | | 1 | | | | DFL-1S-1P-GH1 |
| 11 | TEMP. GAUGE | | 1 | | | | 0~100'C |
| 10 | FAN COOLER | | 1 | | | | FA015 |
| 9 | RETURN FILTER | | 1 | | | | RF TYPE |
| 8 | THROTTLE CHECK VALVE | | 2 | | | | Z2FS6-2-4X/2QV |
| 7 | PILOT CHECK VALVE | | 2 | | | | Z2S6-1-6X |
| 6 | SOLENOID VALVE | | 2 | | | | 4WE6J 6X/EG96N9K4/M+RZ5L |
| 5 | SOL. RELIEF VALVE | | 1 | | | | DBW10B2-5X/315-6EW110N9K4+Z5L |
| 4 | CHECK VALVE | | 2 | | | | S8A 1.0/ |
| 3 | ELECTRIC MOTOR | | 1 | | | | 2.2KW AC440V 3ø 4P 60HZ |
| 2 | PISTON PUMP | | 1 | | | | A10-FR01H-12 |
| 1 | OIL TANK | SS275 | 1 | | | | 170 LITER |
| | HYDRAULIC UNIT | | 1SET | | | | OUT SIDE DRAWING |

나 우 하 이 텍

SCALE 1/5 PROJECTION
SIZE A1 DIMENSION mm

TITLE: PLANT / FACILITY — 방풍 DOOR HYD'UNIT

REF. DWG. NO. — EQUIPMENT: NWHP-170L-LCP-SW; MAKER DWG. NO.: NW-2020-01-SW

| POSCO | DRAWN | CHECKED | REVIEWED | APPROVED | (SUPPLIER) | DRAWN | CHECKED | REVIEWED | APPROVED |
|---|---|---|---|---|---|---|---|---|---|
| SIGNATURE | | | | | | . | . | | |
| DATE | | | | | | . | . | | |

POSCO DWG. NO. .